



FIRE SPECIFICATION CAB CHASSIS - SUITS LC79SC

Multidrive Technology's fire specification cab-chassis fit-out is a custom packaged solution developed wholly for utilisation on Toyota LC79 single cab fire vehicles. There is no compromise on fit, form, or total function. Whatever the appliance – ultra light tanker, quick attack, or general service fire vehicle – Multidrive Technology have all bases covered!

Maximise service body space and payload capacity! Removal of the OEM rear-mounted 130L fuel tank and application of a nearside mid-mounted 100L steel fuel tank which retains optimal OEM fuel gauge accuracy and allows approx. 30kg additional payload. A rear under-chassis mounted spare wheel replaces the OEM fuel tank to maximise space for service body requirements. A 2.5" re-routed stainless-steel exhaust with muffler-delete ensures performance and compliance requirements are maintained. GVM upgrade and rear diff track correction options are included. Multiple additional options are also available for fitment – see the components list.

Multidrive Technology offer both pre-registration fitment under Second Stage Manufacture (SSM) compliance approval, or post-registration fitment via Vehicle Assessment Signatory Scheme (VASS) Engineering Certificate. Assurance is guaranteed that such significant modifications are expertly applied against every vehicle.

Our fire specification cab-chassis package provides an all-inclusive base vehicle setup. Following the addition of a third-party service body and communications of choice, each fleet vehicle is ready for the field.

To find out more, please visit our website.



MODEL APPLICABILITY

Landcruiser 79 (Single Cab) from 10/2016+



WEIGHT RATING

GVM	3780kg / 3950kg	(OEM)
BTC	3500kg	(OEM)
GCM	6900kg	(OEM)
RAC*	2300kg* / 2420kg* / 2500kg*	
FAC	1540kg	

*OEM / MDT Tru Tracker™ track correction

#MDT re-rated OEM housing

*MDT HD track corrected housing



RAISED HEIGHT

Front	25mm STD / 35mm HD
Rear	50mm
Approx. unladen heights only	



TYRE/WHEEL SIZE

265/70R16LT / 16X7JJ / 0	(OEM)
225/95R16C / 16X6J / +20	(OEM)
7.50R16-8PRLT / 16x5.50F / +20	(OEM)
*refer state reg's for allowable deviation	



FUEL CAPACITY

100L (tracked optimally via OEM dash fuel gauge)



COMPONENTS

- GVM upgrade (refer options)
- Rear diff track correction (refer options)
- Mid-mount 100L steel fuel tank (retains OEM gauge)
- Fire protection lagging to rear soft fuel hoses
- Re-routed 2.5" stainless-steel muffler-delete exhaust
- Rear under-chassis mounted spare wheel
- Engine hour meter
- Protector guards
- Front guard rubber flare extensions
- Dual battery (refer options)
- Load rated wheels / tyres (refer options)



WARRANTY

Fleet 1 year / 50,000km







APPROVAL

SSM approval 50404 (NB1 Category)*
*All listed modifications carried by this approval



OTHER SERVICE OPTIONS



RRP \$ [ENQUIRE] installed*

*compliance/engineering additional
*Trade/Dealer/Fleet pricing available



Multidrive Technology

25 Hume Reserve Crt Bell Park, VIC 3215
03 5240 7150